

# LTA-380

## Teller Cash Recycler

---

### Operational Features

- Up to 12 denominations recycling (multi country currency)
- Up to 17,100 notes of storage capacity
- Operational (Transit) cassette is available inside safe for secure note loading and unloading
- Optimally configurable cassette options based on various demands in capacity/denomination
- High precision banknote recognition of images, patterns, etc.
- Unattended self-audit and notes loading/unloading without exposure of operational (transit) cassette

### Unique Features

- Up to 600 notes of rejected notes or physical escrow capacity
- Automatic retract of untaken notes
- Use as desktop note counter, then automatic deposit of counted notes from output pocket
- Entire note path is located outside of safe for increased security and easy maintenance

### Best in Class Security

- Accurate counterfeit notes recognition and 'sort out'
- Note serial number recognition and image capture
- Equipped with international standard certified safe
- Reporting of "duress" note dispense serial numbers and note images

### High Efficiency

- Smallest footprint
- 8" foldable touch screen
- On screen operator training and guidance videos




## LTA-380 Technical Information

Specification*			
Main Control Unit	Intel, Memory 4G, SSD 128G, Windows 10		
User Interface	8" wide LCD with touch screen		
Cash Recycling Module (CRM)	Denominations	Max. 12 Denomination (by Split CST 6EA)	
	Transaction speed (Deposit/ Dispense)	10 ~ 12 notes/sec	
	Cassette capacity**	Recycling CST	Large CST(2,850 notes) up to 6EA, mixed with Split CST Split CST(1,500 + 1,500 notes) up to 6EA, mixed with Large CST
		Operation CST	2,850 notes
		Max. Total	17,100 notes
	Deposit hopper max. capacity	500 notes, Continuous feed	
	Withdrawal hopper max. capacity	300 notes/transaction	
	Retract/ Reject hopper max. capacity	100 notes	
	Reject notes/Physical Escrow	Max capacity 600 notes	
Dimensions	Size (W x H x D)	UL291: 15" x 27" x 44"	
	Weight	UL291: 860 lbs.	
Safe certification	UL291		
Safety {lock}	Dial Lock (option: electronic or key lock)		
Security alarm (optional)	Shock/ Vibration Sensor, Heat Detection Sensor		
Power consumption	Standby	70W	
	Operation	560W	
Noise Level	Standby	46dBA	
	Operation	70dBA	
Power Supply	AC 100-240V		
Environmental conditions	Operation	+5°C to +40°C 25% to 85% relative humidity	

\*Specifications are subject to change without prior notice for product improvement.

\*\*Cassette capacity: Based on 0.01cm thickness note



**ATEC AP**